


DYNAMIC PRECISION



TECHNICAL SPECIFICATIONS

STEREO POWER AMPLIFIER

DPA 5.52

DPA 5.52HP

TECHNICAL SPECIFICATIONS

DPA 5.52

OUTPUT POWER, RMS, 20Hz-20kHz, @ 1% THD (clipping level) :	8 Ω load, 250W per channel 4 Ω load, 500W per channel 2 Ω load, 1000W per channel 8 Ω load, 1000W bridged mono
Maximum output current:	More than 120A per channel (140A peak)
DISTORTION, THD @ 400W 20Hz-20kHz in a 4 Ω load:	Less than 0.0015%
DISTORTION, THD @ 35V RMS, 1 kHz:	Less than 0.00012%
IM DISTORTION, CCIR 13 kHz and 14 kHz, 8 Ω load:	Less than 0.0002% (typical 0.0001%)
FREQUENCY RESPONSE:	DC - 800kHz -3dB DC - 150kHz -0dB
SLEW RATE:	Greater than 250V/us
DAMPING FACTOR:	1000 @ DC – 20kHz/8 Ω
SIGNAL/NOISE RATIO, Ref. 250W/8Ω load:	10Hz-80 kHz 110dB 22Hz-22kHz 119dB 10Hz-CCIR-QPK 110dB IEC-A weighted 119dB
INPUT IMPEDANCE:	100 k Ω (100pF in parallel)
GAIN:	31,7dB (38,4X)
SENSITIVITY:	1,04 V RMS for 200W/8 Ω
CHANNEL SEPARATION:	More than 120dB@ DC -150kHz
COMMON MODE REJECTION RATIO:	Better than 80dB@ DC -150kHz
DIMENSION (W x H x D in mm):	610 x 271x 535
WEIGHT (kg):	85

THD: Total harmonic distortion.
RMS: The Root Mean Square of a voltage.

Dynamic Precision reserves the rights to change or alter the specifications and/or the technical solutions without prior notice.