

**DYNAMIC**  
**PRECISION**



## **TECHNICAL SPECIFICATIONS**

**REMOTE CONTROLLED**

**STEREO PRE-AMPLIFIER**

dpC1s

# dpC1s

## TECHNICAL SPECIFICATIONS

<b>DISTORTION, THD @ 0dBV</b> 20Hz-20kHz in 10K $\Omega$ load:	Less than 0.0001%	
<b>IM DISTORTION, CCIR 13 kHz and</b> 14 kHz, 10K $\Omega$ load:	Less than 0.0002%	
<b>FREQUENCY RESPONSE (filter bypassed):</b>	DC - 200kHz -3dB	
<b>SIGNAL/NOISE RATIO, Ref. 0dBV:</b>	10Hz-80 kHz	105dB
	22Hz-22kHz	112dB
	10Hz-CCIR-QPK	100dB
	IEC-A weighted	114dB
<b>INPUT IMPEDANCE:</b>	100 k $\Omega$	
<b>NUMBER OF BALANCED INPUTS</b>	5	
<b>BALANCED OUTPUT IMPEDANCE:</b>	50 $\Omega$	
<b>MAX GAIN:</b>	10dB (3x)	
<b>MAXIMUM OUTPUT LEVEL:</b>	> +20dBV	
<b>FREQUENCY SETTINGS FOR ROOM EQ</b>	Flat, 32Hz, 60Hz and 80Hz	
<b>CHANNEL SEPARATION:</b>	More than 120dB@ DC -100kHz	
<b>COMMON MODE REJECTION RATIO:</b>	Better than 100dB@ DC -100kHz	
<b>DIMENSION :(W x H x D in mm)</b>	445 x 90 x 383	
<b>MAIN SUPPLY:</b>	1 x 21V~ External power for 230V 240V~ 50-Hz	
<b>WEIGHT :(kg)</b>	5	

THD: Total harmonic distortion.

RMS: The Root Mean Square of a voltage.

***Dynamic Precision reserves the rights to change or alter the specifications and/or the technical solutions without prior notice.***

### Manufacturer

#### **Dynamic Precision AS**

Industriveien 3  
N-2020 SKEDSMOKORSET  
NORWAY

Telephone: +47 95870959 / +47 41318043

Facsimile: +47 63879311

E-mail: [info@dynamicprecision.no](mailto:info@dynamicprecision.no)

Web site: <http://www.dynamicprecision.no/>



# dpC1s

## TECHNICAL SPECIFICATIONS



**C1RC Remote Control**



**dpC1s back panel**

